



# Safety Data Sheet

## Prop BH

Version 1.02

Revision Date 30.10.2023

### SECTION 1. Identification of the substance/mixture and of the company/undertaking

#### Product identifier

**Trade name** Prop BH

**Product code** 2045

#### Relevant identified uses of the substance or mixture and uses advised against

**Use** Solvent.

**Uses advised against** Prohibited for use in production of hand sanitizer.

#### Manufacturer or supplier's details

**Company Address** Sasol Chemicals, a division of Sasol South Africa Ltd  
Sasol Place, 50 Katherine Street  
Sandton  
2090  
South Africa

**Telephone** +27103445000

**E-mail address** sasolchem.info.sa@sasol.com

**Emergency telephone number** +44 (0)1235 239 670 (Europe, Israel, Africa, Americas)  
+44(0)1235 239 671 (Middle East, Arabic African countries)  
+65 3158 1074 (Asia Pacific)  
+86 400 120 6011 (China)  
+27 (0)17 610 4444 (South Africa)  
0800 112 890 RSA-Local only  
+61 (2) 8014 4558 (Australia)

### SECTION 2. Hazards identification

#### Classification of the substance or mixture

##### REGULATION (EC) No 1272/2008

<b>Classification</b>	Flammable liquids	Category 3
	Skin irritation	Category 2
	Serious eye damage	Category 1
	Specific target organ toxicity - single exposure (Central nervous system)	Category 3
	Specific target organ toxicity - single exposure (Respiratory system)	Category 3

#### Label elements

##### REGULATION (EC) No 1272/2008

# Safety Data Sheet

## Prop BH

Version 1.02

Revision Date 30.10.2023

**Hazard pictograms** :



**Signal word** : Danger

**Hazard statements** :

- H226 Flammable liquid and vapour.
- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.

### Precautionary statements

#### Prevention

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

P264 Wash skin thoroughly after handling.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P240 Ground and bond container and receiving equipment.

P233 Keep container tightly closed.

P241 Use explosion-proof electrical/ ventilating/ lighting equipment.

P243 Take precautionary measures against static discharge.

#### Response

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.

P332 + P317 If skin irritation occurs: Get medical advice/ attention.

P305 + P354 + P338 + P317 IF IN EYES: Immediately rinse with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical help.

P370 + P378 In case of fire: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide for extinction.

#### Storage

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

#### Disposal

P501 Dispose of contents/ container to an approved waste disposal plant.

#### Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

# Safety Data Sheet

## Prop BH

Version 1.02

Revision Date 30.10.2023

### SECTION 3. Composition/information on ingredients

#### HAZARDOUS INGREDIENTS

##### Propan-1-ol

**Contents:**  $\geq 40.00$  -  $\leq 60.00$  %W/W

**CAS-No.** 71-23-8

**Index-No.** 603-003-00-0

**EC-No.** 200-746-9

**Hazard statements** H225 H318 H336 H303 H313

##### Butan-2-ol

**Contents:**  $\geq 20.00$  -  $\leq 40.00$  %W/W

**CAS-No.** 78-92-2

**Index-No.** 603-004-01-3

**EC-No.** 201-158-5

**Hazard statements** H319 H335 H336 H226

##### Iso-butanol

**Contents:**  $\geq 10.00$  -  $\leq 25.00$  %W/W

**CAS-No.** 78-83-1

**Index-No.** 603-108-00-1

**EC-No.** 201-148-0

**Hazard statements** H226 H315 H318 H335 H336

##### n-Butanol

**Contents:**  $< 10.00$  %W/W

**CAS-No.** 71-36-3

**Index-No.** 603-004-00-6

**EC-No.** 200-751-6

**Hazard statements** H226 H302 H335 H315 H318 H336

##### 3-Methylbutan-2-ol

**Contents:**  $< 4.00$  %W/W

**CAS-No.** 598-75-4

**Index-No.** 603-006-00-7

**EC-No.** 209-950-2

**Hazard statements** H226 H332 H335

##### Pentan-2-ol

**Contents:**  $< 4.00$  %W/W

**CAS-No.** 6032-29-7

**Index-No.** 603-006-00-7

**EC-No.** 227-907-6

**Hazard statements** H226 H315 H335

# Safety Data Sheet

## Prop BH

Version 1.02

Revision Date 30.10.2023

### SECTION 4. First aid measures

#### Description of necessary first-aid measures

<b>Inhalation</b>	Move to fresh air in case of accidental inhalation of vapours. If breathing is irregular or stopped, administer artificial respiration. Get medical attention immediately
<b>Skin contact</b>	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Get medical attention if irritation develops and persists.
<b>Eye contact</b>	Remove contact lenses. Rinse immediately with plenty of water, also under the eyelids, for at least 5 minutes. Get medical attention immediately
<b>Ingestion</b>	If swallowed, seek medical advice immediately and show this container or label. Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person.
<b>Most important symptoms/effects, acute and delayed</b>	

Refer to SECTION 11

### SECTION 5. Firefighting measures

<b>Suitable extinguishing media</b>	Water spray, Foam, CO2, Dry powder.
<b>Unsuitable extinguishing media</b>	Do NOT use water jet.
<b>Special hazards arising from the substance or mixture</b>	Hazardous decomposition products
<b>Special protective equipment for firefighters</b>	Wear self-contained breathing apparatus and protective suit.

### SECTION 6. Accidental release measures

<b>Personal precautions</b>	Use personal protective equipment. Do not breathe vapours or spray mist. Ensure adequate ventilation. Keep away from sources of ignition - No smoking. Use non-sparking tools. Shut off all sources of ignition.
<b>Environmental precautions</b>	Avoid subsoil penetration. Do not flush into surface water or sanitary sewer system. Should not be released into the environment. Prevent further leakage or spillage if safe to do so. Do not allow material to contaminate ground water system.
<b>Methods for cleaning up</b>	Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). The material taken up must be disposed of in accordance with regulations.
<b>Reference to other sections</b>	Refer to section 8 and 13

# Safety Data Sheet

## Prop BH

Version 1.02

Revision Date 30.10.2023

### SECTION 7. Handling and storage

**Safe handling advice** Wear personal protective equipment. Avoid contact with skin and eyes. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Ensure all equipment is electrically grounded before beginning transfer operations.

**Advice on protection against fire and explosion** No data available.

**Requirements for storage areas and containers** Keep containers tightly closed in a cool, well-ventilated place. Keep away from sources of ignition - No smoking. Provide sufficient air exchange and/or exhaust in work rooms.

**Advice on common storage** No data available.

### SECTION 8. Exposure controls/personal protection

#### Components with workplace control parameters

#### NATIONAL OCCUPATIONAL EXPOSURE LIMITS

Components	Type	Control parameters	Update	Basis
N-PROPANOL	TWA	500 mg/m <sup>3</sup>	1995	South Africa RELs
N-PROPANOL	TWA	200 ppm	1995	South Africa RELs
PROPAN-1-OL	STEL	625 mg/m <sup>3</sup>	1995	South Africa RELs
PROPAN-1-OL	STEL	250 ppm	1995	South Africa RELs
SEC-BUTYL ALCOHOL	TWA	300 mg/m <sup>3</sup>	1995	South Africa RELs
SEC-BUTYL ALCOHOL	TWA	100 ppm	1995	South Africa RELs
	STEL	450 mg/m <sup>3</sup>	1995	South Africa RELs
	STEL	150 ppm	1995	South Africa RELs
ISOBUTYL ALCOHOL	TWA	150 mg/m <sup>3</sup>	1995	South Africa RELs
ISOBUTYL ALCOHOL	TWA	50 ppm	1995	South Africa RELs
	STEL	225 mg/m <sup>3</sup>	1995	South Africa RELs
	STEL	75 ppm	1995	South Africa RELs
BUTAN-1-OL	STEL	150 mg/m <sup>3</sup>	1995	South Africa RELs
N-BUTYL ALCOHOL	STEL	50 ppm	1995	South Africa RELs
BUTAN-1-OL				

#### Exposure controls

##### Engineering measures

Provide sufficient air exchange and/or exhaust in work rooms.

##### Personal protective equipment

**Respiratory protection** Wear self-contained breathing apparatus and protective suit.

**Hand protection** Gloves suitable for permanent contact.:

## Safety Data Sheet

### Prop BH

Version 1.02

Revision Date 30.10.2023

<b>Eye protection</b>	Material: butyl-rubber
<b>Skin and body protection</b>	Break through time: 4 h
<b>Hygiene measures</b>	Material thickness: 0.5 mm
	Safety glasses with side-shields.
	Protective suit. Safety shoes.
	Wash hands before breaks and immediately after handling the product.

#### SECTION 9. Physical and chemical properties

##### Information on basic physical and chemical properties

<b>Form</b>	Liquid
<b>State of matter</b>	Liquid; at 20 °C; 1,013 hPa
<b>Colour</b>	Colourless
<b>Odour</b>	Alcohol-like
<b>Odour Threshold</b>	No data available.
<b>pH</b>	Not applicable.
<b>Melting point/range</b>	No data available.
<b>Boiling point/boiling range</b>	99 - 113 °C
<b>Flash point</b>	27 °C; closed cup
<b>Evaporation rate</b>	No data available.
<b>Flammability (solid, gas)</b>	No data available.
<b>Auto-ignition temperature</b>	No data available.
<b>Decomposition Temperature</b>	No data available.
<b>Lower explosion limit</b>	1.4 %(V)
<b>Upper explosion limit</b>	13.7 %(V)
<b>Vapour pressure</b>	No data available.
<b>Relative vapour density</b>	No data available.
<b>Density</b>	0.805 g/cm <sup>3</sup> ; 20 °C
<b>Solubility/qualitative</b>	Completely soluble
<b>Water solubility</b>	Completely miscible, Completely soluble
<b>Partition coefficient: n-octanol/water</b>	No data available.
<b>Viscosity, kinematic</b>	3.46 mm <sup>2</sup> /s; 20 °C

#### SECTION 10. Stability and reactivity

<b>Reactivity</b>	Stable under recommended storage conditions.
<b>Chemical stability</b>	Stable under normal conditions.
<b>Possibility of hazardous reactions</b>	Heating can release hazardous gases.
<b>Conditions to avoid</b>	Heat, flames and sparks.
<b>Materials to avoid</b>	Oxidizing agents. Reducing agents. Acids and bases
<b>Hazardous decomposition products</b>	No decomposition if stored normally.

#### SECTION 11. Toxicological information

<b>Skin irritation</b>	Propan-1-ol: Rabbit: Not irritating; Draize Test (literature value)
<b>Skin irritation</b>	Iso-butanol: Rabbit: Not irritating; (literature value)

## Safety Data Sheet

### Prop BH

Version 1.02

Revision Date 30.10.2023

<b>Skin irritation</b>	n-Butanol: Rabbit: Irritating; OECD Test Guideline 404 GLP: no; (literature value)
<b>Eye irritation</b>	Propan-1-ol: Rabbit: Highly irritating 24 - 72 h; (literature value)
<b>Eye irritation</b>	Iso-butanol: Rabbit: Irritating (literature value)
<b>Eye irritation</b>	Butan-2-ol: Rabbit: Irritating OECD Test Guideline 405 1 d; GLP: yes; (literature value)
<b>Eye irritation</b>	n-Butanol: Rabbit: Irritating GLP: no; (literature value)
<b>Mutagenicity</b>	Iso-butanol: Experiments showed mutagenic effects in cultured bacterial cells. Ames test: Salmonella typhimurium; with and without; Not mutagenic; (literature value)
<b>Mutagenicity</b>	Propan-1-ol: Ames test: Salmonella typhimurium; Not mutagenic; (literature value)
<b>Mutagenicity</b>	n-Butanol: Ames test: Salmonella typhimurium; with and without; Not mutagenic; OECD Test Guideline 471; GLP: no; (literature value)

## SECTION 12. Ecological information

<b>Toxicity to fish</b>	n-Butanol: flow-through test; Pimephales promelas; 96 h; LC50; 1,730 mg/l; GLP: no; (literature value)
<b>Toxicity to fish</b>	Propan-1-ol: static test; Pimephales promelas; 96 h; LC50; 4,650 mg/l; GLP: no; (literature value)
<b>Toxicity to daphnia and other aquatic invertebrates</b>	n-Butanol: static test; Daphnia magna; 48 h; EC50; 1,983 mg/l; GLP: no; (literature value)
<b>Toxicity to daphnia and other aquatic invertebrates</b>	Propan-1-ol: static test; Daphnia magna (Water flea); 48 h; EC50; 3,644 mg/l; (literature value)
<b>Biodegradability</b>	n-Butanol: aerobic; activated sludge of a predominantly domestic sewage; 3 mg/l; 92 %; 20 d; Readily biodegradable.; GLP: no; (literature value)
<b>Biodegradability</b>	Iso-butanol: aerobic; 100 mg/l; > 70 %; 14 d; Readily biodegradable.; OECD Guideline 301 A (new version); (literature value)
<b>Biodegradability</b>	Propan-1-ol: aerobic; 3 mg/l; 81 %; 20 d; Readily biodegradable.; (literature value)
<b>Mobility in soil</b>	No data available.
<b>Results of PBT and vPvB assessment</b>	This substance is not considered to be persistent, bioaccumulating and toxic (PBT). This substance is not considered to be very

# Safety Data Sheet

## Prop BH

Version 1.02

Revision Date 30.10.2023

persistent and very bioaccumulating (vPvB).

### SECTION 13. Disposal considerations

<b>Product</b>	Disposal should be in accordance with local, regional and national legislations.
<b>Packaging</b>	Dispose of spent product packaging responsibly and lawfully with due consideration for health, safety and the environment.

### SECTION 14. Transport information

#### DG Pictogram



**ADR**  
**UN number:** 1987  
**Class:** 3  
**Packaging group:** III; F1;  
**Proper shipping name:** ALCOHOLS, N.O.S.  
 (n-propanol, butanols)

**RID**  
**UN number:** 1987  
**Class:** 3  
**Packaging group:** III; F1  
**Proper shipping name:** ALCOHOLS, N.O.S.  
 (n-propanol, butanols)

**ADNR**  
**UN number:** 1987  
**Class:** 3  
**Packaging group:** III; F1  
**Proper shipping name:** ALCOHOLS, N.O.S.  
 (n-propanol, butanols)

**IMDG**  
**UN number:** 1987  
**Class:** 3  
**EmS:** F-E, S-D  
**Packaging group:** III  
**Proper shipping name:** ALCOHOLS, N.O.S.  
 (n-propanol, butanols)

**Marine pollutant**  
 Not a Marine Pollutant

**ICAO/IATA**  
**UN number :** 1987  
**Class:** 3  
**Packaging group:** III





## Safety Data Sheet

### Prop BH

Version 1.02

Revision Date 30.10.2023

**Proper shipping name:** ALCOHOLS,N.O.S.  
(n-propanol, butanols)

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** Noxious liquid. NF, (8) n.o.s (Prop BH, contains-n-Propyl alcohol)  
Ship Type: 3

POLLUTION CATEGORY: Y

#### SECTION 15. Regulatory information

##### Safety, health and environmental regulations/legislation specific for the substance or mixture

<b>USA TSCA Inventory</b>	All chemical constituents are listed in: USA TSCA Inventory (See chapter 3)
<b>Canadian Domestic Substances List (DSL)</b>	All chemical constituents are listed in: Canadian Domestic Substances List (DSL) (See chapter 3)
<b>Australian Inv. of Chem. Substances (AICS)</b>	All chemical constituents are listed in: Australian Inv. of Chem. Substances (AICS) (See chapter 3)
<b>New Zealand Inventory of Chemicals (NZIoC)</b>	All chemical constituents are listed in: New Zealand Inventory of Chemicals (NZIoC) (See chapter 3)
<b>Jap. Inv. of Exist. &amp; New Chemicals (ENCS)</b>	All chemical constituents are listed in: Jap. Inv. of Exist. & New Chemicals (ENCS) (See chapter 3)
<b>Japan. Industrial Safety &amp; Health Law (ISHL)</b>	All chemical constituents are listed in: Japan. Industrial Safety & Health Law (ISHL) (See chapter 3)
<b>Korea. Existing Chemicals Inventory (KECI)</b>	All chemical constituents are listed in: Korea. Existing Chemicals Inventory (KECI) (See chapter 3)
<b>Philippines Inventory of Chemicals and Chemical Substances (PICCS)</b>	All chemical constituents are listed in: Philippines Inventory of Chemicals and Chemical Substances (PICCS) (See chapter 3)
<b>China Inv. Existing Chemical Substances (IECSC)</b>	All chemical constituents are listed in: China Inv. Existing Chemical Substances (IECSC) (See chapter 3)

#### SECTION 16. Other information

##### Full text of H-Statements

H225 Highly flammable liquid and vapour.  
H226 Flammable liquid and vapour.  
H302 Harmful if swallowed.  
H303 May be harmful if swallowed.  
H313 May be harmful in contact with skin.  
H315 Causes skin irritation.



## Safety Data Sheet

### Prop BH

Version 1.02

Revision Date 30.10.2023

- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.

All reasonable efforts were exercised to compile this SDS in accordance with the Globally Harmonized System of Classification and Labelling of Chemicals (GHS). The SDS only provides information regarding the health, safety and environmental hazards at the date of issue, to facilitate the safe receipt, use and handling of this product in the workplace and does not replace any product information or product specifications. Since Sasol and its subsidiaries cannot anticipate or control all conditions under which this product may be handled, used and received in the workplace, it remains the obligation of each user, receiver or handler to, prior to usage, review this SDS in the context within which this product will be received, handled or used in the workplace. The user, handler or receiver must ensure that the necessary mitigating measures are in place with respect to health and safety. This does not substitute the need or requirement for any relevant risk assessments to be conducted. It further remains the responsibility of the receiver, handler or user to communicate such information to all relevant parties that may be involved in the receipt, use or handling of this product. Although all reasonable efforts were exercised in the compilation of this SDS, Sasol does not expressly warrant the accuracy of, or assume any liability for incomplete information contained herein or any advice given. When this product is sold, risk passes to the purchaser in accordance with the specific terms and conditions of sale.