

B & R PRODUCTS (PTY) LTD

Supreme Paint Suppliers (Pty) Ltd

Reg. No. 80/09849/07

Manufacturers and Distributors of Top Quality Paints and Solvents

P.O. BOX 1633
RANDBURG
2125
SOUTH AFRICA

PHONE: 027 11 864-1301/1302
027 11 864-1036/1393
FAX: 027 11 864-1390
WEB SITE: www.bandr.co.za
E-MAIL : bandr@icon.co.za

Director: B. J. Rodd

PRODUCT DATA SHEET SANDING SEALER

<u>PRODUCT NAME:</u>	SANDING SEALER
<u>FINISH:</u>	MATT
<u>COLOUR:</u>	CLEAR
<u>VEHICLE TYPE:</u>	ALKYD NITROCELLULOSE
<u>PIGMENT TYPE:</u>	INORGANIC AND ORGANIC PHTHALOCHROMES
<u>SOLVENT TYPE:</u>	AROMATIC AND ALIPHATIC HYDROCARBONS, ESTERS, KETONES AND ALCOHOLS
<u>FLASH POINT MIN:</u>	-4°C
<u>SPECIFIC GRAVITY:</u>	0.900 – 1.090 AT 25°C MIXED
<u>SOLIDS CONTENT:</u>	35 – 40% BY WEIGHT MIXED
<u>THINNING RATIO:</u>	+ - 1 TO 1 BY VOLUME
<u>RECOMMENDED THINNER:</u>	B&R LACQUER THINNER
<u>VISCOSITY OF BASE AT 25°C:</u>	850 - 900 cpu
<u>DRYING TIME:</u>	<u>SURFACE:</u> 5 MINUTES AT 25°C
	<u>HARD:</u> 30 MINUTES AT 25°C
<u>APPLICATION METHOD:</u>	CONVENTIONAL SPRAY OR AIRLESS SPRAY.
<u>APPLICATION VISCOSITY:</u>	CONVENTIONAL GUN OR PRESSURE POT: 18 – 20" FORD CUP 4
<u>FINENESS OF GRIND:</u>	10 MICRONS
<u>RECOMMENDED DRY FILM THICKNESS:</u>	20 – 30 MICRONS PER COAT

DESCRIPTION & GENERAL USE:

A top quality sealer for general industrial use on steel, wood, some plastics and fiberglass. Surfaces must be thoroughly cleaned and prepared to accept this primer. The product must be used in a well-ventilated area only.

Automotive Lacquer continued/...

PRODUCT SAFETY DATA

FLASH POINT	:	<5°C
HIGHLY FLAMMABLE	:	Always store in a cool place. If set alight, use only powder fire extinguishers.
SKIN CONTACT	:	Wash immediately with lots of soap and water
EYE CONTACT	:	Rinse with lots of water and seek medical attention as soon as possible.
IF INGESTED	:	Do not induce vomiting. Seek medical attention immediately.